NIC©R[®] select

° [

0

Under Cabinet Series NUC5 Select



LED under cabinet solutions Enhanced ambiance and efficiency



NUC5 Select LED Under Cabinet

NICOR LED under cabinet lighting is an attractive upgrade that can guickly increase the value and functionality of your work space. The NUC5 now offers a CCT Selectable design which allows for easy adjustment to 2700K, 3000K, or 4000K. The NUC5 presents a clean, professional look allowing you to use an existing wall switch or dimmer to easily control your lights. Offering uniform illumination, warm color and low operating temperatures, this under cabinet light can be used in residential, retail, and commercial applications.

Whether in a kitchen, under a shelf or

in a defined work space, these 1-inch low profile fixtures are perfect for task or accent lighting and illuminating products, apparel or collectibles.



Electrical Access

Easy-open door with positive latch makes electrical installation simple

Multiple Knockouts

Versatile knockouts for multidirectional wiring or linkable capped parts enable for quick daisy-chaining to other fixtures



Easy Installation

Pre-installed captive screws allow for quick mounting

Diffuser

Specially designed diffuser prevents pixilation and provides uniform illumination

Low Profile Design

1-inch height keeps the fixture unobtrusive and out of view

NUC5 Select LED Under Cabinet Features

Construction

- Extruded aluminum housing for durability and ample heatsinking
- Low 1-inch profile keeps the fixture unobtrusive and out of view
- No UV or forward-projected heat
- UL Listed for damp locations

Optical System

• Uniform lighting with specially designed glass diffuser to prevent pixelation and "hot spots" on counter tops

Electrical

- Dimmable with most TRIAC dimmers
- Custom low-profile driver engineered for optimal dimming across all sizes
- Operating temperature rating of 0°F to 120°F (-18°C 49°C)
- 120VAC Input

LED

- CCT Selectable at 2700K, 3000K, or 4000K
- Greater than 92 CRI with R9 greater than 50
- L70 rated for greater than >50,000 hours
- TM-21 Projected L70(6k) life >100,000 hours
- LM-79, LM-80 testing performed in accordance with IESNA standards

Finish

Available in: Black, Nickel, White, and Oil-Rubbed Bronze

Installation

- Easy surface mount installation
- Pre-installed captive screws allow for quick mounting
- Positive latch door for easy access and installation
- Versatile knockout selection allows for multidirectional wiring

Warranty

• 5-year limited system warranty standard



Ordering Inform	nation		Example: NUC521SWH	
Series	Version	Length	сст	Housing Color
NUC	5	08 (8 inches)	S (Select)	BK (Black)
		12 (12 ½ inches)		NK (Nickel)
		21 (21 ½ inches)		OB (Oil-rubbed bronze)
		30 (30 inches)		WH (white)
		40 (40 Inches)		

All reports based on current industry standards; field performance may differ from laboratory performance Specifications and dimensions subject to change without notice.

FINISH OPTIONS

1

WH BK NK OB

PRODUCT INFORMATION				
Product Specs	NUC5			
TM-21 Calculated L70(6K) hours:	>100,000 hours			
Power Draw at full power:	8" - 3.63W 12.5" - 5.25W 21.5" - 8.66W 30" - 11.06W 40" - 15.52W			
Input Voltage :	120VAC			
Dimensions:	Height: 1" Width: 3.5" Length: Varies			



	Length Dimensions (I	L)
	Inches	Millimeters
NUC508	8	203
NUC512	12.5	317
NUC521	21.5	546
NUC530	30	762
NUC540	40	1016

Warehouse Locations

- Albuquerque, NM Atlanta, GA Detroit, MI Folcroft, PA Houston TX
- Indianapolis, IN Lombard, IL Miami, FL Syracuse, NY Van Nuys, CA

T 800.821.6283 F 800.892.8393 www.nicorlighting.com

2200 Midtown Pl. NE Albuquerque, NM 87107 USA





LIT-NUC5-Select-10PK 20191118 ©2019 NICOR® • ALL RIGHTS RESERVED

