Copernico 500 suspension polished red

1608048A



Design By

Carlotta de Bevilacqua

Collection — Design



Specifications

specifications	
Delivered lumens	1963lm
Light output ratio	85.35lm/W
Power consumption	23W
Led type	21W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>80
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire
Input Voltage	120-277V
Driver	ADVANCE - 1 x XI050C100V054XPL1

Colors & Finishes

Polished Red RAL3020

Materials =

• Made in anodized aluminum

Features & Accessories =

Packaging =

1 Box

• 7 concentric mobile rings obtained from an aluminum plate support a circuit of 384 LEDs

• The rings rotate independently on two different axes enabling light to be directed

• Numerous spatial configurations can be obtained by adjusting the rings as needed

1 x 21-15/16" x 21-9/16" x 5" / 10.36 lbs - 55.5 cm x 54.5 cm x 12.5 cm / 4.7 kg

• When the device is closed up it is completely flat

Also compatible with 0-10V dimming

Dimensions =




standard length min. 19 ^{11/16} - max. 78 ³⁴ min. 50 cm - max. 200 cm extended length min. 19 ³⁴ - max. 216 " min. 50 cm - max. 548 cm

19^{5/16}" 49 cm

Light distribution —

Direct/Indirect




Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane

Luminaire weight

6.17 lbs / 2.8 kg

Warranty 5 year limited warranty



We reserve the right to change specifications of our products. For the latest product information please visit www.artemide.net

