SINGLE SPOT

Endurance Wallpack

WAC LIGHTING

Responsible Lighting®



SPECIFICATIONS

Construction: Die-cast aluminum **Power:** Line Voltage input (120V)

Fixture Type:

Project:

Location:

Catalog Number:

CRI: 85

Dimming: 100% - 10% with Electronic Low Voltage (ELV) dimmer

Finish: Architectural Bronze, Graphite and White

Standards: Energy Star*, IP66, Wet Location, ETL & cETL Listed **Operating Temperature:** -40°C (-40°F) to 40°C (104°F)

Rated Life: 43,000 hours


PRODUCT DESCRIPTION

Die cast aluminum factory sealed housings with patent pending design for a water and dust proof IP66 rated outdoor luminaire

FEATURES

- IP66 and ETL & cETL Wet Location Listed
- Factory-Sealed LED Light Engine
- Energy Star® rated
- Die-Cast Aluminum Construction
- 120V Direct Wire No Driver Needed
- Photo/Motion Sensor Sold Separately
- Smooth and Continuous ELV Dimming

PHOTOMETRY



ORDER NUMBER

WP-LED415 15W 75W Halogen 30 3000K 965 550 585 aBZ Architectural Bronze aGH Architectural Graphite aWT Architectural White		Power	Comparable	Colo	or Temp	Delivered Lumens	СВСР	Finish	
	WP-LED415	15W	75W Halogen	30 50			550 585	aGH	Architectural Graphite

Example: WP-LED415-30-aBZ

ACCESSORIES



Photocell Sensor

PC-120-BZ PC-120-GY PC-120-WT Bronze Gray White

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 **Headquarters/Eastern Distribution Center**44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585