# ASSEMBLY INSTRUCTIONS (For LD18731-1)

## WARNING!

Olf cushion gets wet, hang over chair to dry to prevent mold/mildew.

## ATTENTION:

- 1. Please read these instructions carefully before assembly.
- 2. Since aluminum is soft metal, over tightening may strap thread or break the parts.

## 3. DO NOT use power tools.

- Assembly steps:
- Loosely attach the seat and back frame(A&B) to the arms(C&D) with bolt(H&G),flat washers(I) lock washer(J), and PVC cover(L). DO NOT tighten the nuts.
- 2. Turn the chair onto its legs and put the cushion on (F&F1)then it is ready to use.

Warning : Do not use acid or alkaline washing liquid to clean the product.



**\* NO SOCKET DRIVERS** 



# ASSEMBLY INSTRUCTIONS (For LD18731A-48)

#### ATTENTION:

- 1. Please read these instructions carefully before assembly.
- 2. Since aluminum is soft metal, over tightening may strap threads or break the parts.
- 3. DO NOT use power tools.
- 4. Check parts against the parts list to make sure you have all parts needed for proper assembly.
- 5. Familiarize yourself with the inventory of parts and the accompanying illustrations to ensure safe and proper assembly.

### Assembly step:

- 1. Loosely attach the leg connector bracket (B) to the legs by using the screws(E) flat washers(F), lock washers(E), and pvc cover(H).
- Turn the table top(A) upside down on the soft clean surface, attach the complete base onto the table top by using the screws(D) flat washers(F), lock washers(E).
- 3. Tighten all the screws and nuts completely. DO NOT over tighten the nuts and screws.

4. Turn the table onto its legs and use the adjuster feet to level the tables.

Warning : DO NOT use acid or alkaline washing liquid to clean the product.

