

Armillary Sphere Chandelier

Item # SC5102

WE RECOMMEND INSTALLATION OF THIS LIGHTING FIXTURE BE DONE BY A LICENSED ELECTRICIAN.

WARNING \*\*\* SWITCH OFF THE MAIN ELECTRICAL SUPPLY FROM THE MAIN FUSE BOX/CIRCUIT BREAKER BEFORE INSTALLATION.

INSPECT ITEM CAREFULLY BEFORE ATTEMPTING TO INSTALL. IF THERE IS ANY DAMAGE OR OBVIOUS DEFECT, DO NOT INSTALL.

ITEM MAY NOT BE RETURNED ONCE IT HAS BEEN INSTALLED.

- 1. Screw top loop onto top threaded rod of fixture body, and tighten at side of top loop until tight.
- 2. Screw arrow head and end of arrow both ends of the rod.
- Attach chain to top loop chandelier. Feed wire through chain and mounting loop. Slide canopy on chain.
- Insert top thread nipple loop to nipple. Insert top thread nipple in mounting 1/4 IPS pipe. Attach chain mounting loop to nipple.
- 5. Attach chain with ficture to chain mounting loop at desired height.
- 6. Attach ground (silver or copper on color) fixture wire to ground wire from ceiling outlet box (usually green or copper in color), and fasten together with a plastic wire connector. Tightly wrap the wire connector with electrical tape so the end of the connector is sealed.

IT IS IMPERATIVE THAT THE OUTLET BOX IN YOUR HOME BE PROPERLY GROUNDED.

- Connect neutral (RIBBED, without any markings) fixture wire to the neutral (usually white) wire from ceiling outlet box. Fasten both wires together with plastic wire connector and tightly wrap the wire connector with electrical tape.
- Repeat procedure with the hot (ROUND, with UL markings) wires. Always make sure that no wire strands are left outside the connectors.
  DO NOT REVERSE THE HOT AND NEUTRAL CONNECTIONS OR SAFETY WILL BE COMPROMISED.
- 9. Connect the safety steel wire from the fixture and the safety cable from ceiling with lock nut.
- 10. Slip canopy to ceiling and secure with threaded canopy ring.
- 11. Insert light bulbs (not included) into the sockets.

VISUAL COMFORT & CO. Est. 1987