



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Features

This ultra low profile design provides a dramatic look and features an edge-lit light panel construction. Products can be used in various applications including corridors, closets, bath, showers, hallway, kitchen and anywhere general lighting is needed.
 Indoor use only - Wall or ceiling mount.
 Outdoor use only - Covered ceiling mount.



Construction

Edge-lit technology housing is injection molded with steel backplate.
 Twist and lock bracket.
 Mounts to standard junction box (not included).
 Power supply connections must be made inside junction box.

Finish

White or Black finish.

Diffuser

White acrylic.

Electrical

D1 Driver

Input 120 VAC, 60 Hz. The LED driver is dimmable with a 2-wire (TRIAC) or electronic low voltage (ELV) dimmer switch.

D2 Driver

Input 120-277 VAC 60 Hz. LED driver is dimmable with 0-10V dimmer.

Lamping

Integrated LED modules capable of producing:
 25W = 2700 source lumens, 2200 delivered lumens
 42W = 4500 source lumens, 3700 delivered lumens
 Adjustable Choice 3000K, 4000K, 5000K (CCT). Preset at 3000K.
 Rated for 50,000 Hrs. 90 CRI.

Certification

cETLus listed
 ENERGY STAR® Qualified
 Title 24/JA8 Compliant
 Wet location rated for indoor use. Outdoor wet location rated for covered ceiling mount applications ONLY (not recommended for any other outdoor use).
 Suitable for use in clothes closets when installed in accordance with the NEC 410.16 spacing requirements.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions
 subject to change without notice.

Ordering Information:

White	Black	LED	Source Lumens	Delivered Lumens	Adjustable CCT	DIA.	D
EGRF1625LAJD1WH	EGRF1625LAJD1BK	25W	2400	1900	3000K/4000K/5000K	15-5/8"	15/16"
EGRF1625LAJD2WH	EGRF1625LAJD2BK	25W	2400	1900	3000K/4000K/5000K	15-5/8"	15/16"
EGRF2440LAJD1WH	EGRF2440LAJD1BK	42W	3600	3375	3000K/4000K/5000K	23-5/8"	1"
EGRF2440LAJD2WH	EGRF2440LAJD2BK	42W	3600	3375	3000K/4000K/5000K	23-5/8"	1"

