

KSF-1610

Single Handle Commercial Style Pull Down Sensor Kitchen Faucet

Faucet Dimensions

Overall Height: 18 3/4"
 Spout Height: 6 1/4"
 Spout Reach: 8 5/8"

Features

- Commercial Style Pull Down Sensor Faucet
- Metal Body
- ABS Sprayer
- Lead Free Braided Nylon Waterway
- 180° Swivel Spout
- Flow Rate: 1.8 gpm (6.8L/min) @ 60 psi
- Dual Function Sprayhead - Spray/Stream
- 35mm Ceramic Cartridge
- 36" Integrated Nylon Waterlines
- Sensor operated (open handle first) with 3 minute automatic shutoff
- Coin slot switch on control box to make faucet mechanical
- Dome Shaped Screen Washer
- Swivel Sprayer Connector
- Quick Weight
- Quick Connect Sprayer Hose
- 16" Hose Length
- Connections 3/8" Compression
- Max Deck Thickness: 3 1/2"
- TPI of aerator in the Sprayer - M24*1

Accessories Included

- Weight
- Hex Wrench
- Control Box
- Battery Housing
- Battery

Optional Accessories (sold separately)

- AC Adapter

Available Finishes

- Matte Black
- Spot Free Stainless Steel
- Brushed Brass
- Brushed Brass/Matte Black
- Spot Free Stainless Steel/Matte Black

CODES/STANDARDS:

Product Certification

cUPC (ASME A112.18.1/CSA B125.1)
 NSF/ANSI Standard 61 and 372 certified by IAPMO
 AB1953, MASS, DOE, CEC, ADA

NOTE: Some Kitchen Faucets that do not have a pull out or pull down sprayer may be connected to a portable dishwasher. Pull out and pull down faucets should never be connected to portable dishwashers because potential pressure fluctuations during washing cycles cause hose ruptures or leaks.

Warranty

Kraus Limited Lifetime Warranty
 see website for details www.kraususa.com

