# Cariddi wall/ceiling/floor 41W 20° 3000K anthracite

## SPECIFICATIONS



## Design By Ernesto Gismondi

Collection — Outdoor



### Colors & Finishes

Anthracite grey

#### Materials =

- Body in aluminum
- Silicon-sealed silk-screened tempered glass
- Optical unit made of a PMMA lens and an anodized aluminum reflector

Delivered lumens2322lmLight output ratio56.63lm/WPower consumption41WLed type38W C.O.B.*CCT (Correlated Color Temperature)300KCRI (Color Rendering Index)>80Life expectancy0n/OffInput Voltage120VDriverTCI - 1 x X20600713BUG Rating83-U0-G0	Specifications	
Power consumption41WLed type38W C.O.B.*CCT (Correlated Color Temperature)3000KCRI (Color Rendering Index)>80Life expectancy50000HrsControl typeOn/OffInput Voltage120VDriverTCI - 1 x X206000713	Delivered lumens	2322lm
Led type38W C.O.B.*CCT (Correlated Color Temperature)3000KCRI (Color Rendering Index)>80Life expectancy5000HrsControl type0n/OffInput Voltage120VDriverTCI - 1 x X206000713	Light output ratio	56.63lm/W
CCT (Correlated Color Temperature) 3000K   CRI (Color Rendering Index) >80   Life expectancy 50000Hrs   Control type On/Off   Input Voltage 120V   Driver TCI - 1 x X206000713	Power consumption	41W
CRI (Color Rendering Index)     >80       Life expectancy     50000Hrs       Control type     On/Off       Input Voltage     120V       Driver     TCI - 1 x X206000713	Led type	38W C.O.B.*
Life expectancy     50000Hrs       Control type     On/Off       Input Voltage     120V       Driver     TCI - 1 x X206000713	CCT (Correlated Color Temperature)	3000K
Control type     On/Off       Input Voltage     120V       Driver     TCI - 1 x X206000713	CRI (Color Rendering Index)	>80
Input Voltage     120V       Driver     TCI - 1 x X206000713	Life expectancy	50000Hrs
Driver     TCI - 1 x X206000713	Control type	On/Off
	Input Voltage	120V
BUG Rating B3-U0-G0	Driver	TCI - 1 x X206000713
	BUG Rating	B3-U0-G0

#### Features & Accessories =

• Consists of an adjustable lighting unit and terminal board

- Rotation on base +/-180°, body tilting on bracket +/-130°, allowing accurate adjustment
- Positioning is maintained by means of locking dowels

• Electronic driver integrated

- Standard non dimmable
- For dimming options, please consult with your Artemide Sales Representative

#### Dimensions -



#### Light distribution —

Direct



Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane

Luminaire weight = 8.26 lbs / 3.75 kg

Warranty

Marranty

5 year limited warranty



### Packaging

1 Box

1 x 20" x 13-3/8" x 14-3/8" / 11.58 lbs - 50.7 cm x 33.7 cm x 36.3 cm / 5.252 kg