

**Description:** Quiet DC (Direct Current) bathroom fan with adjustable speed control (50-80-110 CFM) engineered for continuous run • Fits 2"x4" construction • Ceiling or wall mount • Suitable for new construction or remodeling • HVI certified • ENERGY STAR certified • ETL/cETL listed for use in insulated ceilings (Type I.C.).

**Motor/Blower:** Brushless high performance DC motor engineered for continuous energy efficient operation; power rating 120v/60Hz; motor equipped with thermal shut off.

**Housing:** Galvanized steel body; 4" oval duct connector; built-in back draft dampener; patented quick mounting anti-vibration bracket included; designed for installation in ceilings with minimum of 4" clearance.

Grille: Low maintenance, wipe clean; attaches to housing with torsion springs.

Finish: White (W)

Ventilating Area: For bathrooms up to 110 sq ft.

**Installation:** Must be installed by licensed professional. Complete installation instructions included.

## Warranty: 6 Years

**Architect's Specifications:** Ventilation fan will be ceiling mount, ENERGY STAR qualified, adjustable speed of 50-80-110 CFM, with no less than 80 CFM and no more than 0.4 Sones as certified by HVI at 0.1 static pressure in inches water gauge. Power consumption shall be no greater than 7.4 watts and ENERGY STAR rated with an efficiency rating of no less than 10.9 CFM/watt. The motor will be enclosed brushless DC motor engineered for continuous operation. CFM switch tab will allow for 3 separate airflow (CFM) settings for 4" oval duct. Fan shall be listed for tub/shower enclosure when used with GFCI branch circuit wiring and shall be ETL/cETL listed for use in insulated ceiling (Type I.C.). Fan shall be ASHRAE 62.2, LEED, California Title 24, and Washington VIAQ compliant.








Specifications

## ABFS 0511 D6 Series

## Low Profile Adjustable Speed Ceiling/Wall Bathroom Fan



## ETL/cETL Listed for installation over tub/shower enclosure when used with GFCI circuit wiring



D6 (W) Grille

Model: ABF 0511 D6 Series	4" Duct	
Static Pressure (inches w.g.)	0.1	0.25
Air Volume (CFM)	80	80
Noise (sones)	0.4	0.9
Power Consumption (Watts)	7.4	11.5
Energy Efficiency (CFM/Watts)	10.9	7.0
Speed (RPM)	852	1100
ENERGY STAR rated	Yes	
Grille Dimensions	13" x 13"	

Model	Qty	Comments	Project
			Location
			Architect
			Engineer
			Contractor
			Submitted by
			Date

Aero Pure, LLC • 1006 Bankton Circle Ste B • Hanahan, SC 29410 • 843.377.8642 www.aeropurefans.com