RUBIX - model: FM-W25

LED Ceiling Mount

WAC LIGHTING

Responsible Lighting®

Fixture Type:
Catalog Number:
Project:
Location:

PRODUCT DESCRIPTION

Precise engineering using the latest energy efficient LED technology with a built-in reflector for superior optics; An appealing cylindrical profile with a powerful LED down light perfect for accent and wall wash lighting. PD-W2605 is supplied with 3 x 12" and 1 x 6" stems and the canopy has a hang straight swivel mount for sloped ceilings.

FEATURES

- Wall or Ceiling Mount
- · IP65 Rated, ETL & cETL Wet Location Listed
- Die-Cast Aluminum Construction
- Universal Voltage Input (120V 277V)
- Dimming: ELV (120V) or 0-10V

SPECIFICATIONS

Construction: Aluminum with etched glass.
Power: Integral driver in luminaire. 120V - 277V input.
Light Source: High output LED
Mounting: Mounts directly to junction box
Dimming: 0-10V Dimming: 100%-10%
ELV Dimming: 100%-15% (120V only)
Finish: Brushed Aluminum (AL), Black (BK), Bronze (BZ), Graphite (GH), White (WT)
Color Temp: 3000K
CRI: 90
Rated Life: 70,000 hours
Standards: IP65 Rated, ETL & CETL Wet Location Listed, Dark Sky Friendly.

	I	Beam	Photometry	Voltage	Watt	Lumens	Finish
5″ · 5″ · 5″ · 5″	FM-W2505	86°	XXX	120V - 277V	16W	750	AL Brushed Aluminum BK Black
	FM-W2510	95°	XXX	120V - 277V	30W	1875	BZ Bronze GH Graphite WT White

Example: FM-W2510-WT

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050 **Western Distribution Center** 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. JUL 2017