

# **MERICH**

## **MATTY® 6032 LH ADA**

Always check the website for the most updated specifications: www.americh.com









All bathtub dimensions are  $\pm 1/2$ "

### **Builder Series**



## **Luxury Series**



### **DIMENSIONS**

 $60'' \times 32'' \times 18''$  (1524 × 813 × 457 mm) Whirlpool Operating Gallons = 40 (Liters = 151) Gallon to Overflow = 60 (Liters = 227)

**MATERIAL:** Acrylic (All Americh Standard Colors)

TUB FLOOR: Textured

**Undermount:** No


### **Platinum Series**



(pump and blower location only)



Airbath System II



Airbath System III

N/A

> JET

- ACCESS PANEL (MINIMUM 16" X 20")

ON/OFF CONTROL

ROTARY JET

## **ELECTRICAL REQUIREMENTS**Americh recommends one 20 amp

Americh recommends one 20 amp ground fault circuit interrupter (GFCI) for each power supply provided with the bathtub.

### **STANDARD EQUIPMENT:**

- Apron
- Molded Tile Flange
- Adjustable Feet

### **OPTIONAL ACCESSORIES**

- Chromatherapy\*
- Grab Bars: Madison\*
- High Density Insulation\*
- iBath Sound System
- Inline Heater (whirlpool only)
- Jets: Additional or Rotary\*
- Ozone System (whirlpool and/or Airbath only)
- Pillows: 12" \* Angle
- Remote Control Upgrade (select series only)
- Syllent Pump with Heated Air\*
- Thermal Comfort System (TCS cannot be used with VSM)
- Trim Kit Upgrade\*
- Vibro Sonic Massage (VSM cannot be used with TCS)
- Waste & Overflows Upgrades

(\*) Standard on Platinum Series (+) Standard on Luxury Series

- Cable Drive Waste & Overflow\*
- PVC Waste & Overflow<sup>+</sup>
- Linear Waste & Overflow

### INSTALLATION TIPS

LEGEND: P PUMP

• Install according to Owner's Manual and local codes.

GRAB BAR

- Airbath III units may be 11/2" 21/2" higher than stated.
- Any whirlpool or Airbath® unit requires an access panel.
- Hot water supply should be 65-75% of tub capacity or greater.

**BLOWER** 

- Always consult your local plumber for recommendations as installations will vary.
- The combination of multiple systems and options may require components to stick out and/or be remotely installed in the field.

#### **CODES AND COMPLIANCE**

Americh products meet or exceed the following standards:

- Underwriters Laboratories (UL)
- Underwriters Laboratories Canada (cUL)
- Canadian Standards Association (CSA)
- ANSI Z124.1 ANSI A112-19.7
- ANSI A112.19.8

Contact Americh for additional approvals.

