



Cast Iron Wallmount Sinks

Installation

Faucets, drains and wall brackets are not installed and will require assembly. Depending on your local ordinance, the installation may be required to be performed by a licensed plumber. Professional Installation is always recommended. To install a wall mount sink:

BEFORE INSTALLING WALL-MOUNT SINK INSTALLATION (mounting bracket included) 1. Place the mounting bracket in the installation location and mark the wall through each of the mounting holes. Important: The sink should be anchored to two wall studs. Locate and mark the position of the wall studs to which you will fasten your sink by listening for a solid sound as you knock on the wall or by using a stud finder. If the studs in your bathroom do not line up to the mounting location for your sink, wood blocking can be installed between the studs using standard 2 x 4's. 2. Drill mounting holes for the anchor or lag bolts using the bracket as guides. If the wall is tile, use a masonry drill bit. 3. Secure the mounting bracket(s) to the wall with the anchor bolts. After inserting the first fastener, verify that the bracket is level. When the bracket(s) is properly aligned insert the remaining fasteners. 4. Install the new faucet and drain assembly according to the installation instructions. 5. Attach the sink to the wall and brackets with the mounting hardware. 6. Connect the water supply and drain lines. Turn on the water supply to check for any leaking from the water supply lines or sink basin.

Care & Maintenance Instructions

Do:

Clean gently: warm water and liquid detergents (non-abrasive) cleansers such as Ivory or Dawn with a soft sponge or cloth – Rinse and wipe down. For Stainless steel rim – Bar Keepers friend polishes nicely.

Don't:

Don't use steel wool or scrubbing pad or abrasive cleansers for cleaning.

Don't allow drain opening chemicals, nail polish remover, bleach or other harsh products to touch the finish.

Don't leave leaky faucets to continue dripping for long periods of time, as mineral deposits may build up or erode enamel.

Warranty information

Limited lifetime warranty against manufacturer's defects. Is not for damage to finish (enamel) due to mistreatment or mis-use/abuse of surface. Email inquiries to: Info@NantucketSinksUSA.com