

Obice mini wall 18°

T430418W28

SPECIFICATIONS



Design By

Alessandro Pedretti

Collection

Outdoor



Specifications

| | |
|------------------------------------|---------------------------------------|
| Delivered lumens | 505lm |
| Light output ratio | 72.14lm/W |
| Power consumption | 7W |
| Led type | 7W Array* |
| CCT (Correlated Color Temperature) | 3000K |
| CRI (Color Rendering Index) | >80 |
| Life expectancy | 50000Hrs |
| Control type | On/Off |
| Input Voltage | 24VDC |
| Driver | Remote power supply (sold separately) |
| BUG Rating | B1-U0-G0 |

Colors & Finishes

☐ White


Materials

- Body in injection molded aluminum
- Terminal base and adjustable joint in injection molded aluminum
- Diffuser in 1/64" (4mm)-thick tempered glass with black opal serigraphy

Features & Accessories

- Tilting angle +35°/-125°
- Rotation on horizontal axis 359°
- Wiring to be carried out by means of a plug located in the terminal base
- Standard non dimmable
- For dimming options, please consult with your Artemide Sales Representative
- nh S3 2 arms (1578058A-SP0169)
- Transformer 24vDC 60W 120v (TE01-11575)

Dimensions




Packaging

1 Box

1 x 12-11/16" x 12-11/16" x 8-9/16" / 4.33 lbs - 32 cm x 32 cm x 21.5 cm / 1.965 kg

Light distribution

Direct



Red = Max Cd. Through Vertical plane

Blue = Max Cd. Through Horizontal plane

Luminaire weight

2.79 lbs / 1.27 kg

Warranty

5 year limited warranty