


**WYND** 52" Ceiling Fan  
FR-W1801-52L

MODERN FORMS  
SMART FANS



**PRODUCT DESCRIPTION**

Transitional style meets smart technology with this versatile smart fan available in four weather-resistant finishes as well as a 316 marine-grade stainless steel for harsh outdoor climates. The 42 inches is ideal for bedrooms, patios and breakfast nooks while the 52 inches works great in living rooms and medium-sized spaces. The LED luminaire, powered by WAC, takes this design from beautiful to brilliant. Connect with our exclusive Modern Forms app for even more life enhancements.

**SPECIFICATIONS**

- Construction:** Aluminum
- Blade:** 13° Pitch, 52" sweep, ABS
- Downrod:** 1" O.D. x 4.5"H included
- Mounting Slope:** Up to 30°
- Lead Wire:** 80"
- Hanging Weight:** 17.5 lbs
- Total Power:** 54.5W
- Standards:** ETL/cETL Wet Location listed

**FEATURES**

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Optional LED light kit included
- Includes RF wall control
- Additional RF wall control for 3, 4-way control sold separately
- Compatible with Modern Forms app

**LIGHT KIT PERFORMANCE**

- Light Source:** LED
- Light Wattage:** 19.5W
- Dimming:** Integrated
- Color Temperature:** 3000K
- Rated Life:** 50,000 Hours
- Standards:** Title 24 JA8-2016 compliant

**ESTIMATED AIR PERFORMANCE**

- Airflow:** 6568 cubic ft per minute on high
- Power:** 35 watts on high
- Airflow Efficiency:** 188 cubic ft per minute per watt
- Revolutions Per Minute:** 168 RPMs on high/105 RPMs on average

**WIRELESS PERFORMANCE**

- RF Pairing Distance:** Up to 30 ft from fan
- Wi-Fi Range:** Up to 150 ft\*

**ORDER NUMBER**

Model	LED Lumens	Delivered Lumens	Housing	Blade
FR-W1801-52L	1600	846	<b>BZ</b> <i>Bronze</i>	<i>Bronze</i>
			<b>GH</b> <i>Graphite</i>	<b>WG</b> <i>Weathered Gray</i>
			<b>MW</b> <i>Matte White</i>	<i>Matte White</i>
			<b>SS</b> <i>Stainless Steel</i>	<i>Stainless Steel</i>

Example: **FR-W1801-52L-GH/MW**

\*Results may vary based on application and surroundings.



modernforms.com  
Phone (866) 810.6615  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760

**OPTIONAL ACCESSORIES**

	<p><b>RF Wall Control</b></p> <p><b>F-WC</b></p>	<p><b>WT</b> White</p>	<p>Control fan speed, light brightness and switch between Summer and Winter Modes from up to 30 ft away. One RF Wall control comes standard with each Modern Forms Smart fan.</p>
	<p><b>Wi-Fi Touch Panel Wall Control</b></p> <p><b>F-TS</b></p>	<p><b>BK</b> Black <b>WT</b> White</p>	<p>Sold separately. Android tablet comes pre-loaded with Modern Forms app, Wi-Fi range up to 150 ft from router. Results may vary based on application/surroundings.</p>
	<p><b>Downrod</b></p> <p><b>XF-12</b> 12in <b>XF-18</b> 18in <b>XF-24</b> 24in <b>XF-36</b> 36in <b>XF-48</b> 48in <b>XF-60</b> 60in <b>XF-72</b> 72in</p>	<p><b>AS</b> Automotive Silver <b>BZ</b> Bronze <b>CFI</b> Carbon Fiber** <b>DW</b> Dark Walnut <b>GB</b> Gloss Black <b>GH</b> Graphite <b>GW</b> Gloss White <b>MB</b> Matte Black <b>MW</b> Matte White <b>OB</b> Oil Rubbed Bronze <b>SS</b> Stainless Steel <b>TT</b> Titanium Silver</p>	<p>All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.</p>
	<p><b>Downrod Couplers</b></p> <p><b>XF-I</b></p>		<p>Connects two downrods together.</p>
	<p><b>Sloped Ceiling Kit</b></p> <p><b>XF-SCK</b></p>		<p>Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.</p>

Examples: RF Wall Control - **F-WC-WT**, Wi-Fi Touch Panel - **F-TS-WT**, Downrod - **XF-12-BZ**, Downrod Coupler - **XF-I-BZ**, Sloped Ceiling Kit - **XF-SCK-DW**

**NOTE:** Recommended maximum downrod length of 72" with 80" lead wire.

\*\*Carbon Fiber downrods available in 12", 18", 24" and 36"

**SUGGESTED DOWNROD HEIGHT USAGE**

<b>Ceiling Height</b>	15'	14'	13'	12'	11'	10'	9'
<b>Downrod</b>	72"	60"	48"	36"	24"	18"	12"

**SLOPED CEILING DEGREE CONVERSION CHART**

<b>Degree</b>	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
<b>Ceiling Slope Pitch</b>	1/12 pitch	2/12 pitch	3/12 pitch	4/12 pitch	5/12 pitch	6/12 pitch	7/12 pitch	8/12 pitch	9/12 pitch	10/12 pitch	11/12 pitch	12/12 pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.