ASSEMBLING & INSTALLATION INSTRUCTIONS PRODUCT# 20234 20238 20244 20248 20254 OUTDOOR POST MOUNT LIGHT FIXTURE

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER. ASSEMBLING THE FIXTURE (Fig.1). Fig.1 1. Carefully unpack new fixture and lay all the parts on a clear surface. Take care not to lose any small parts necessary for installation. 2. Please open the window(B), raise the candle sleeve(A) on the lamp holder. Install the bulbs in accordance with the fixture's specifications. DO NOT EXCEED THE MAXIMUM WATTAGE RATING! Finally close the window, lock bolt. 3. Attach the assembly lamp body onto the post (no included) and lock it securely with the screw(C). Wiring (Fig.2) 1. Connect the electrical wires as follows. Connect the black wire from the fixture to the black house (hot) wire. Connect the white wire from the fixture to the white (neutral) house wire. Make sure all wire nuts are secured. You may wrap the connections with electrical tape. If your outlet box has a ground wire (green or bare copper) connect fixture's ground wire to it. Otherwise attach the bare copper fixture wire to the green ground screw on the circular strap. 2. Tuck the wire connections neatly into the junction box. C. -Fixture Wire Fixture Ground Wire Supply Wire Supply Ground Wire (No included) Your installation is now complete. Return power to the junction box and test the fixture. Fig.2 FIXTURE FIXTURE FIXTURE WIRES WIRES WIRES Black or White or Bare Smooth Ribbed Copper HOUSE (Ground) HOUSE HOUSE

WIRES

Green or

Bare Copper (Ground)

WIRES

White

(Neutral)

WIRES

Black

(Hot)

