

Features

- Freestanding design creates a striking focal point in your bathing area.
- Sloped lumbar support on both ends.
- 18-inch bathing depth offers a deep soaking experience.
- Wide deck along one side simplifies installation and provides support for getting in and out of bath.
- Straight shroud.
- Textured bottom surface.
- Center drain.

Material

Acrylic.

Installation

Freestanding.

Recommended Products/Accessories

K-7265 Clearflo Bath Drain K-37383 Rough-in cable bath drain, PVC, 30" cable with tubing K-37386 rough-in cable drain, PVC, 30" cable K-24916 Wireless Music Kit K-T37391 Bath Cable Drain Trim K-T37392 Bath Cable Drain Trim K-T37393 Bath Cable Drain Trim K-T37394 Bath Cable Drain Trim K-T37395 Bath Cable Drain Trim K-T37396 Bath Cable Drain Trim K-T37397 Cable Bath Drain Trim K-23726 Drain treatment K-23732 Tub & shower cleaner



Codes/Standards

CSA B45.5/IAPMO Z124 ASTM E162 ASTM E662

KOHLER[®] Plastic Baths and Receptors Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White

•	
96	Biscuit



Stargaze® Freestanding Bath K-24010



Stargaze® Freestanding Bath K-24010

No change in measurements if connected with drain illustrated. (K-7265)



Technical Information

All product dimensions are nominal.		
Installation:	Freestanding	
Drain location:	Center	
Basin area, bottom:	40-5/16" x 22-1/2" (1024 mm x 572 mm)	
Basin area, top:	49-3/8" x 25-7/8" (1254 mm x 657 mm)	
Weight:	156 lbs (70.8 kg)	
Minimum floor load:	54 lbs/ft² (263.7 kg/m²)	
Water depth:	18" (457 mm)	
Water capacity:	60 gal (227.1 L)	
Template:	Footprint, 1364289, not required, not included	

Notes

Measure your actual product for rough-in details. Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

