

Edge Round LED Surface Mount Disc Light **EGRF Series**

Features

This ultra low profile design provides a dramatic look and features an edge-lit light panel construction. Products can be used in various applications including corridors, closets, bath, showers, hallway, kitchen and anywhere general lighting is needed. Indoor use only - Wall or ceiling mount. Outdoor use only - Covered ceiling mount.

Construction

Edge-lit technology housing is injection molded with steel backplate. Snap-in bracket. Mounts to standard junction box (not included). Power supply connections must be made inside junction box.

Finish

Choose from white, satin nickel, or black finish.

Diffuser

White acrylic.

Electrical

Direct wired with a constant current low voltage electronic LED driver rated at 120 VAC. The driver is dimmable down to 10% of full scale with a 2-wire (Triac) or electronic low voltage (ELV) dimmer switch.

Lamping

Fixture includes a LED modules capable of producing: 12W = 900 source lumens, 745 delivered lumens 15W = 1125 source lumens, 1034 delivered lumens 22W = 1650 source lumens, 1574 delivered lumens 3000K (CCT). Rated 24/7, working temperature: -20°C ~ 45°C for 50,000 Hrs. 90 CRI.

Certification

cETLus listed ENERGY STAR® Qualified Title 24/JA8 Compliant Wet location rated for indoor use. Outdoor wet location rated for covered ceiling mount applications ONLY (not recommended for any other outdoor use). Suitable for use in clothes closets when installed in accordance with the NEC 410.16 spacing requirements.

Options - Sold Separately

Retrofit Kit for 4" and 6" ceiling cans. Battery back-up (EGRF-BB08) for 8" models. Spacer Pan (EGRF-BB08PAN) for 8" models.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.

Ordering Information:

Satin Nickel		
EGRF0609L30D1SN		
EGRF0811L30D1SN		
EGRE1216L30D1SN		

.Kei	winte
09L30D1SN	EGRF0609I
11L30D1SN	EGRF0811L3
6L30D1SN	EGRF1216L3

e	Black
F0609L30D1WH	EGRF0609L30D1BK
F0811L30D1WH	EGRF0811L30D1BK
F1216L30D1WH	EGRF1216L30D1BK

Accessory Kit



EGRF-RET04 For use in converting 4 in. round ceiling cans



EGRF-RET06 For use in converting 6 in. round ceiling cans

ССТ

3000K

3000K

3000K

DIA

5-3/8'

8"

12'

D

3/4"

3/4"

3/4

Delivered Lumens

745

1034

1574

Source Lumens

900

1125

1650



EGRF-BB08 Battery back-up (8 in. model only) (white only)



EGRF-BB08PAN Spacing Pan (8 in. model only)











LED

12W

15W

22W