## Cariddi wall/ceiling/floor 41W 40° 4000K anthracite T418740N08

Design By =

Ernesto Gismondi

Collection =

Outdoor

## **SPECIFICATIONS**



• Silicon-sealed silk-screened tempered glass

• Optical unit made of a PMMA lens and an anodized aluminum reflector

Colors & Finishes

Anthracite grey

Materials = • Body in aluminum

# D . @ us (P65)

#### Specifications = **Delivered lumens** 2405lm Light output ratio 58.66lm/W Power consumption 41W 38W C.O.B.\* Led type CCT (Correlated Color Temperature) 4000K CRI (Color Rendering Index) >80 Life expectancy 50000Hrs On/Off Control type 120V Input Voltage TCI - 1 x X206000713 Driver B2-U0-G0 **BUG Rating**

### Features & Accessories

• Consists of an adjustable lighting unit and terminal board

- Rotation on base +/-180°, body tilting on bracket +/-130°, allowing accurate adjustment
- · Positioning is maintained by means of locking dowels

• Electronic driver integrated


• Standard non dimmable

Packaging = 1 Box

• For dimming options, please consult with your Artemide Sales Representative


1 x 20" x 13-3/8" x 14-3/8" / 11.58 lbs - 50.7 cm x 33.7 cm x 36.3 cm / 5.252 kg

### Dimensions =



Light distribution =

Direct



Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane Luminaire weight = 8.26 lbs / 3.75 kg

Warranty -5 year limited warranty

10 1/16"

ø13.5 cm 6 1/4" 7.6 cm 16 cm

last updated: 2020-06-30

We reserve the right to change specifications of our products. For the latest product information please visit www.artemide.net

# Artemide