DOLCECLIMA® S1 14HP UL





The powerful **hi-tech** portable air-conditioner **designed** in **Italy**,

the ideal solution for your well being in every season thanks to its heat pump function.

With the motorized flap you can set the air flow as you like it, for an improved thermal comfort.

01911

77.2/88.0





REMOTE CONTROL







Product code

Cooling (DOE)

Barcode		8021183019117
Power supply	V-Ph-Hz	115V,1Ph,60Hz
Capacity	Btu/hr	14000
Input	W	1415
Current	Α	12,3
EER	W/W	2.9
	Btu/W.h	
Capacity	Btu/h	11000
Input	W	1170
Current	Α	10.2
COP	W/W	2.76
SACC	Btu/h	9000
Input	W	1300
Current	Α	11.3
Standby power_DOE	W	1.45
Off-cycle_DOE:	W	82
Moisture Removal (35/28.3)	L/h	2.68
Starting current	Α	54
Indoor side air flow (Hi/Mi/Lo)	m³/h	520/480/443
	CFM	306/283/261
Indoor side noise level(Hi/Mi/Lo)	dB(A)	56/54/52
Refrigerant type / quantity	/oz	R410A /19,78
Plug type		LCDI(5-15P)
Power cord type	AWG	14x3
Power cord length	mm	1900
Power cord length	ft	6,2
Control type		Remote Control
Operation temp (room temp.)	°C	17-35/5-30
	°F	41-86
Application area Cooling Standard)	m ²	19-27
Application area Cooling Standard)	sq.ft	205-291
recommended room size	sq.ft	500
Dimension (W*D*H)	mm	490x425x765
	in	19.3/16.7/30.1
Packing (W*D*H)	mm	535x487x890
	in	21.1/19.2/35
Net/Gross weight	Kg	35.0/39.9

FEATURES

Cooling capacity: 14.000 BTU/hr EER: 2,9 Practical wheels Practical side handles Refrigerant gas: R410A Touch LCD display

FUNCTIONS

- Fanmode Adjustable 3 fan speed. Fan only mode can also be used.
- ♦ Dehumidification
- Atto mode

Automatic operation which regulates cooling in relation to the ambient temperature to optimize energy consumption.

Sleep mode Gradually increases the temperature set and ensures reduced noise for greater wellbeing at night.

Turbo mode

Maximum fan
speed. Extra cool.