



Lighting Your Life Since 1970

## Product Specifications - 41426WGGO

Job Name:	Job Type:
Quantity:	Comments:



### 41426WGGO Camden VX 3-Light Outdoor Wall Lantern

#### Finish

Golden Bronze

#### Glass/Shade

Water Glass

#### Product Category

Outdoor Wall Mount

#### Lamping

Number of Bulbs	3
Light Type	Incandescent
Bulb Type	CA
Max Bulb Wattage	60
Max Fixture Wattage	180
Rated Life	±1,500 Hours
Rated Lumens	±2,016
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard Dimmer

#### Measurements

Width	13.0"
Height	29.0"
Length	N/A
Extension	17"
Back Plate Width	6.5"
Back Plate Height	14.5"
HCO	16.0"
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	13.2 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

#### Shipping

Carton Weight	13.2 lbs
Carton Width	19"
Carton Height	16"
Carton Length	37"
Carton Cubic Feet	6.59
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

#### Certification

Safety Rating	Wet
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No
Dark Sky	N/A

#### Other

UPC Code	783209064027
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	Vivex

#### Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.