


ELF 38" Ceiling Fan
FR-W1802-38L

MODERN FORMS
SMART FANS



PRODUCT DESCRIPTION

From bedrooms to boardrooms, pool houses to patios, Elf works its magic with a compact design that looks great anywhere- even outside. We make all our smart fans wet-rated- that means highly durable materials and weather-resistant finishes- so you can keep a consistent look and feel throughout your décor. Control your smart fan with the exclusive Modern Forms app, which integrates easily with smart devices you already own- if you want to turn it on, all you have to do is ask.

SPECIFICATIONS

- Construction:** Aluminum
- Blade:** 13° Pitch, 38" sweep, ABS
- Downrod:** 1" O.D. x 4.5"H included
- Mounting Slope:** Up to 30°
- Lead Wire:** 80"
- Hanging Weight:** 15 lbs
- Total Power:** 63.5W
- Standards:** ETL/cETL Wet Location listed

FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Optional LED light kit included
- Includes RF wall control
- Additional RF wall control for 3, 4-way control sold separately
- Compatible with Modern Forms app

LIGHT KIT PERFORMANCE

- Light Source:** LED
- Light Wattage:** 23.5W
- Dimming:** Integrated
- Color Temperature:** 3000K
- Rated Life:** 50,000 Hours
- Standards:** Title 24 JA8-2016 compliant

ESTIMATED AIR PERFORMANCE

- Airflow:** 5257 cubic ft per minute on high
- Power:** 40 watts on high
- Airflow Efficiency:** 132 cubic ft per minute per watt
- Revolutions Per Minute:** 247 RPMs on high/120 RPMs on average

WIRELESS PERFORMANCE

- RF Pairing Distance:** Up to 30 ft from fan
- Wi-Fi Range:** Up to 150 ft*

ORDER NUMBER

| Model | LED Lumens | Delivered Lumens | Housing | Blade |
|--------------|------------|------------------|----------------------------------|------------------------|
| FR-W1802-38L | 2041 | 949 | BZ <i>Bronze</i> | <i>Bronze</i> |
| | | | MW <i>Matte White</i> | <i>Matte White</i> |
| | | | TT <i>Titanium Silver</i> | <i>Titanium Silver</i> |

Example: **FR-W1802-38L-BZ**

*Results may vary based on application and surroundings.



modernforms.com
Phone (866) 810.6615
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

OPTIONAL ACCESSORIES

| | | |
|--|--|---|
| <p>RF Wall Control</p>  <p>F-WC</p> | <p>WT White</p> | <p>Control fan speed, light brightness and switch between Summer and Winter Modes from up to 30 ft away. One RF Wall control comes standard with each Modern Forms Smart fan.</p> |
| <p>Wi-Fi Touch Panel Wall Control</p>  <p>F-TS</p> | <p>BK Black WT White</p> | <p>Sold separately. Android tablet comes pre-loaded with Modern Forms app, Wi-Fi range up to 150 ft from router. Results may vary based on application/surroundings.</p> |
| <p>Downrod</p>  <p>XF-12 12in XF-18 18in XF-24 24in XF-36 36in XF-48 48in XF-60 60in XF-72 72in</p> | <p>AS Automotive Silver BZ Bronze CFI Carbon Fiber** DW Dark Walnut GB Gloss Black GH Graphite GW Gloss White MB Matte Black MW Matte White OB Oil Rubbed Bronze SS Stainless Steel TT Titanium Silver</p> | <p>All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.</p> |
| <p>Downrod Couplers</p>  <p>XF-I</p> | | <p>Connects two downrods together.</p> |
| <p>Sloped Ceiling Kit</p>  <p>XF-SCK</p> | | <p>Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.</p> |

Examples: RF Wall Control - **F-WC-WT**, Wi-Fi Touch Panel - **F-TS-WT**, Downrod - **XF-12-BZ**, Downrod Coupler - **XF-I-BZ**, Sloped Ceiling Kit - **XF-SCK-DW**

NOTE: Recommended maximum downrod length of 72" with 80" lead wire.

**Carbon Fiber downrods available in 12", 18", 24" and 36"

SUGGESTED DOWNROD HEIGHT USAGE

| Ceiling Height | 15' | 14' | 13' | 12' | 11' | 10' | 9' |
|----------------|-----|-----|-----|-----|-----|-----|-----|
| Downrod | 72" | 60" | 48" | 36" | 24" | 18" | 12" |

SLOPED CEILING DEGREE CONVERSION CHART

| Degree | 4-8° | 9-13° | 14-17° | 18-21° | 22-25° | 26-29° | 30-32° | 33-35° | 36-38° | 39-41° | 42-44° | 45° |
|---------------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|-------------|-------------|-------------|
| Ceiling Slope Pitch | 1/12 pitch | 2/12 pitch | 3/12 pitch | 4/12 pitch | 5/12 pitch | 6/12 pitch | 7/12 pitch | 8/12 pitch | 9/12 pitch | 10/12 pitch | 11/12 pitch | 12/12 pitch |

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.