



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Allen LED Vanity ALNV Series

Features

White patterned linen acrylic front panel provides a soft glow accent to this contemporary vanity. The finished trim ends identify the graceful shape. Top diffuser and bottom diffuser are frosted white acrylic.

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

All metal parts are finished in satin nickel or oil-rubbed bronze. Internal housing is finished in a lighting grade baked white enamel.

Diffuser

Diffuser is 0.070" thick white linen pattern acrylic front. Frame mounts to electrical channel with two decorative screws.

Electrical

Input 120-277 VAC/60Hz
Compatible with 0-10V dimmers.

LED

Integrated LED modules capable of producing:
29" - 26W, 2000 source lumens
41" - 35W, 3000 source lumens
53" - 49W, 4000 source lumens
Adjustable Choice 3000K, 3500K, 4000K (CCT).
Rated for 50,000 Hrs. 90 CRI.

Certification

cETLus listed for damp locations.
ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions
subject to change without notice.

Ordering Information:

Satin Nickel	Oil-Rubbed Bronze	LED	Source Lumens	Adjustable CCT	L	H	D
ALNV280520LAJD2SN	ALNV280520LAJD2RB	26W	2000	3000K/3500K/4000K	29-1/2"	4-1/2"	3-3/4"
ALNV400530LAJD2SN	ALNV400530LAJD2RB	35W	3000	3000K/3500K/4000K	41-1/2"	4-1/2"	3-3/4"
ALNV540540LAJD2SN	ALNV540540LAJD2RB	49W	4000	3000K/3500K/4000K	53-1/2"	4-1/2"	3-3/4"



3in1 color temperature
3000K/3500K/4000K

