



PRODUCT DETAILS:

- Wattage settings includes: 3W (260 Lumens), 5W (350 Lumens), 8W (475 Lumens), 12W (750 Lumens)
- Three lens options offer versatility in beam spread via an easy to remove and insert assemble - includes: 20° Spot, 40° Flood, 60° Flood
- Suitable for use in wet (outdoor direct rain or sprinkler) locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards
- Photometrics based off engine photometrics.
- Incorporates CREE LEDs with application performance tested by CREE
- Optional performance lenses available
- LumaCore Series products carry a lifetime limited warranty
- Hardy Island Series products carry a lifetime limited warranty

GRILL TOP WELL LIGHT

15705MZ-LMA27K

VARIABLE OUTPUT LED 2700K WELL LIGHT

DETAILS	
FINISH:	Matte Bronze
MATERIAL:	Cast Brass and Aluminum
GLASS:	Clear Lens

DIMENSIONS	
WIDTH:	4.8"
HEIGHT:	4.8"
DEPTH:	4.8
WEIGHT:	3lb

LIGHT SOURCE	
LIGHT SOURCE:	Integrated LED
LED NAME:	30G4SE-12W
VOLTAGE:	12v
COLOR TEMP:	3000
CRI:	80
INCANDESCENT EQUIVALENCY:	1 x 60w, 45w, 35w, 25w
DIMMABLE:	No

MOUNTING	
LEAD WIRE:	1 X 96"

SHIPPING	
CARTON LENGTH:	7
CARTON WIDTH:	7
CARTON HEIGHT:	13.5
CARTON WEIGHT:	4.5

HINKLEY

HINKLEY
33000 Pin Oak Parkway
Avon Lake, OH 44012

PHONE: (440) 653-5500
Toll Free: 1 (800) 446-5539

hinkley.com