HR3D-R09

3" Duo 2.0 Glare Reducing Warm-Dim LED downlight



A spot light at the maximum light output for task becomes a wide distribution ambient light source as it dims down

PRODUCT DESCRIPTION

Glare-reducing dual-source LED downlight

FEATURES

- Trims and housing included
- Reduces overhead glare in the aperture with a warm dimming mixing chamber
- Offered in two warm dimming CCT ranges from 2700K to 2200K and 3000K to 2200K
- 52° cut-off angle
- ELV dimming see specification sheet for list of tested dimmers
- Rated Life: 50,000 hours

MODEL (Trims and Housing included)

- 51/8'
 ~ <u> </u>
D

WAC LIGHTING

Responsible Lighting®

Fixture Type:	
Catalog Number:	
Project:	

SPECIFICATIONS

Construction: Durable die-cast aluminum construction

Input: 120VAC

Power Consumption: 15W

Dimming: ELV Dimming. Lutron Maestro MAELV-600 is recommended.

Mounting: Two heavy gauge retention clips hold trim firmly

Finish: Powder coated white

Standards: ETL & cETL Listed

		At the brightest output			At the lowest output				
		Color Temp	Lumen	Beam Spread	CRI	Color Temp	Lumen	Beam Spread	CRI
New Construction	HR3D-RO92722S-N-WT	2700K	810	20°	90+	2200K	15	120°	90+
	HR3D-RO93022S-N-WT	3000K	890	20°	90+	2200K	15	120°	90+
Remodel	HR3D-RO92722S-R-WT	2700K	810	20°	90+	2200K	15	120°	90+
	HR3D-RO93022S-R-WT	3000K	890	20°	90+	2200K	15	120°	90+

HR3D-RO9____22S-___-WT

Example: HR3D-R092722S-N-WT

	041/8	Model	Input	Notes
	$ \begin{array}{c} \begin{array}{c} \begin{array}{c} \begin{array}{c} \end{array} \\ \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\$	New Construction IC-Rated, Airtight	120V	Ceiling thickness: ½"—1"
	³ ⁄ ₄ " − 24" max − ¹ / ₁ + 10000000000000000000000000000000000	Remodel Non-IC, Airtight	120V	Ceiling thickness: ½"-1"
vaclighting com	Hoodquarters /Fastern Distribution	Contor Control Distri	hutian Cantan	Wostorn Distribution Contor

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. JUL 2017

-2 ³ /4"	Project:
	Location:

3" Duo 2.0 Glare Reducing Warm-Dim LED downlight



waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760