FILIO SPECIFICATION

Customer Service: 1-800-460-7019 www.fluidfaucets.com

Specifications

- . Heavy brass construction for durability and reliability
- Dual handle operation allows both volume and temperature control.
- German made Fluehs ceramic cartridge ensures life long trouble free service
- Pull/push type diverter allows a quick water flow switch from spout to hand shower or vise versa.
- Rough-in valve can be installed separately .
- Trim parts can be installed and serviced above the mounting deck without touching rough-in valves.
- 4 hole 6"-16" widespread installation
- Requires Dual Handle Widespread Deck Mount Tub Filler with Diverter F2005B which is sold separately

Flow Rate

- 15 gpm (56L/min) @ 60 psig for spout
- 2.0 gpm @ 60 psig for hand shower

Finish

- CP (Polished Chrome) .
- PVD-BN (PVD Brushed Nickel)
- PVD-PN (PVD Polished Nickel)

Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- ADA
- IAPMO / cUPC Listed

Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.











fluid Oceanside Series **Dual Handle Widespread Tub Filler Trim Set with Hand Shower**

Model: F2313T

SSI Sustainable Solutions International 8395 Riverbend Court, Burnaby, BC V3N 5E7, Canada

