

Honesty®

Rite-Temp® Bath and Shower Valve Trim K-T99763-4

Features

- Includes valve trim, bath spout, showerarm with flange, and showerhead.
- Single lever handle controls both on/off activation and temperature setting
- Includes 6-5/8" non-diverter bath spout with 1/2" NPT or slip-fit connection.
- Integrated push button diverter.
- Coordinates with Honesty faucets and accessories to complete your bathroom.
- Pressure-balancing diaphragm technology maintains outlet temperature within +/-3 degrees Fahrenheit during water pressure fluctuations.
- 2.0 gpm (7.6 lpm) showerhead with Katalyst™ Spray Technology.
- Showerhead features MasterClean[™] sprayface for easy cleaning.

Material

- Premium material construction with metal handle ensures reliability and durability.
- KOHLER finishes resist corrosion and tarnishing.

Installation

Trim set requires valve to complete installation.

Required Products/Accessories

K-11748 Series Rite-Temp® Valves

Adapters, Rough-in and Extension Kits 1226074-CP









Codes/Standards

ASME A112.18.1/CSA B125.1 DOE - Energy Policy Act 1992 EPA WaterSense®

KOHLER® Faucet Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color Code Description


CP Polished Chrome





Honesty®

Rite-Temp® Bath and Shower Valve Trim



Technical Information

All product dimensions are nominal.

Valve body: Machined-brass

Showerhead/Body Spray:

Rated maximum flow: 2 gal/min (7.6 l/min) Pressure: 45 psi (3.1 bar)

Notes

Install this product according to the installation guide.

Install straight pipe or tube drop of 7" (178 mm) to 18" (457 mm) with single elbow between the valve and the wall-mount spout. Elbow must be a 90 degree drop ell that is secured to rigid framing.

