

KATIE 10 / 12

FLUSH MOUNT CEILING

location:

SPECIFICATIONS:

DESCRIPTION

Flush-mounted round ceiling luminaires, featuring handcrafted glass. Two sizes available.

LAMPING

Standard: 60W A19 120V incandescent, suitable for dimming, not included.
CFL: 13W 4-Pin CFL with non-dimming electronic ballast. 120V, lamp not included.
GU24 CFL: Self-ballasted GU24 lampholders. 13W max, 120V, lamp not included.
LED: 10W GU24 LED Lamp 120V, dimmable, included.
Consult factory for other CFL configurations., CFL lamps not included.

DIFFUSER

Handcrafted ribbed glass diffuser is available in Opal Matte decor. **Katie 10 #945107:** 10.5" Dia. x 3.75" H **Katie 12 #945007:** 12" Dia. x 4.5" H

CONSTRUCTION

Glass diffuser is secured to fitter with three set screws. Stamped aluminum fitter is powder coated white.

MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture. 90°C supply wire required for incandescent lamping.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



KATIE CEILING SHOWN IN OPAL MATTE



DECOR	- LAMP OPTIONS	- OPTIONS		
945107C 10.5" Dia. Opal Matte	(blank) 1x 60W A19 Incar	n LW Low Wattage		
	D1 1x 13W Quad 120	V labeling		
	GU24 1x 13W GU24 120	V		
	LED 1x 10W LED 120V			
	dimmable			

Katie 12: #9450



DECOR	LAMP OPTIONS	- OPTIONS	
945007C 12.0" Dia. Opal Matte	(blank) 2x 60W A19 Incan	LW Low Wattage	
	D2 2x 13W Quad 120V	labeling	
	GU24 2x 13W GU24 120V		
	LED 2x 10W LED 120V,		
	dimmable		

LED 120V PENDANTS:

Total power of only 10 wattsDimmable with a standard dimmer

Rated life: 30,000 hours
Frosted acrylic diffuser

800 lumens
CCT: 2800° Kelvin

CRI: 80+

• Internal driver integrated in the lamp, GU24 base

Ex. 945007C Katie 12 Ceiling w/ Opal Matte Glass

Project Information	n:		
L			

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

Besa Lighting Co., Inc. • 6695 Taylor Rd. • Blacklick, OH 43004 • tel 614-475-7046 • fax 614-475-7048 • www.besalighting.com

REV 10/14