Assembly Instruction Sheet #0417PT9-1-101 For Style 0417PT9-1-101

Tools Required: Flathead screwdriver, Phillips screwdriver, pliers, wire cutters, wire strippers, electrical tape, safety glasses.

Light Source: (1) F26 Base Bulb 60W Maximum(Not Include).

Estimated Assembly Time: 15-30 minutes

Preparation: Identify and inspect all parts before beginning installation. Check package content list and diagrams below to be sure all parts are present. If any parts are missing or damaged, do not attempt to assemble, install, or operate the fixture. Contact customer service for replacement parts.

▲ Warnings and Cautions

Turn off electricity at circuit breaker or main fuse box before installation. Consult a licensed electrician if in doubt.

These instructions are provided for your safety. It is very important you read them completely before installing the fixture. We strongly recommend that a licensed, professional electrician perform the installation.


Disconnect fixture from power source before replacing bulbs. Make sure bulbs are given sufficient time to cool before removal.

Package Contents





STEP 1



Hardware Contents

 PART
 DESCRIPTION QUANTITY

 AA
 Finial
 1pcs

 BB
 Wire nut
 3pcs


 CC
 Screw+Cap Nuts
 2pcs



STEP 2


A loosen the screw.

B.Remove the styrofoam from the Fixture Body.




STEP 3

A.Install bulbs into sockets and screw snug into place.




STEP 5

A. Wire Connections




STEP 4

A.Lock the screw.



STEP 6

A. Lock screws from the side.



2 of 4

ReleasedDate:2021-01-15

3 of 4

ReleasedDate:2021-01-15