Nuda 100 unilateral floor white

T083808

| | Design By Ernesto Gismondi | Specifications | |
|---|----------------------------------|--|---|
| | Lifiesto dismondi | Delivered lumens | 306lm |
| | | Light output ratio | 18lm/W |
| | Collection | Power consumption | 17W |
| | Outdoor | Led type | 6X14.7W Array* |
| | | CCT (Correlated Color Temperature) | 3000K |
| | | CRI (Color Rendering Index) | >80 |
| | | Life expectancy | 50000Hrs |
| | CED c (1) us (1965) | Control type | On/Off |
| Colors & Finishes | | Input Voltage | 120-277V |
| White RAL9002 | | Driver | MAGTECH - 1 x LP1026-36-C0700 |
| | | BUG Rating | B0-U3-G1 |
| Materials Body in aluminum UV resistant diffuser in shock resistant pol | lycarbonate | Electronic driver integrated in bodyStandard non dimmable | ector for the main connections round fixing by means of included lock bolts and dow with your Artemide Sales Representative |
| Dimensions 6 ⁵⁸ " 1 ⁷⁸ " 16.8 cm 4.8 cm | | Packaging 1 Box 1 x 46-1/8" x 11-7/8" x 8-3/16" / 16.62 lbs - 117 cm x 30 cm x 20.5 cm / 7.54 kg | |
| 39. ³⁰ " 100 cm 5. ¹⁰ " 13 cm 7. ^{11/6} " 19.5 cm | | | |
| Light distribution | Luminaire weight | | |
| Direct | 11.49 lbs / 5.21 kg | | |
| Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane | Warranty 5 year limited warranty | | |

