FLOOD - model: WP-LED3

Endurance Wallpack



Responsible Lighting®

Fixture Type:	
Catalog Number:	
Project:	
Location:	



IP66, WET

Includes Two Canopy Accessories for

Surface Mount or Recessed Junction Boxes

Construction: Die-cast aluminum Power: Line Voltage input (120V) Dimming: 100% - 10% with Electronic Low Voltage (ELV) dimmer Finish: Architectural Bronze, White and Graphite Standards: IP66, Wet Location, ETL & cETL Listed Operating Temperature: -40°C (-40°F) to 40°C (104°F)

PHOTOMETRY



• 85 CRI

	Power	Comparable	Color Temp	Delivered Lumens	CBCP	Finish
WP-LED335	35.5W	100W HID	30 3000k 50 5000k		1477 1642	aBZ Architectural Bronze aGH Architectural Graphite aWT Architectural White
Example: WP-LED336-30-BZ	_					

ACCESSORIES

Motion Sensor (120V)	MS-120-BZ MS-120-GY MS-120-WT	Bronze Gray White		Photo Sensor (120V)	PC-120-BZ PC-120-GY PC-120-WT	Bronze Gray White
-------------------------	-------------------------------------	-------------------------	--	------------------------	-------------------------------------	-------------------------

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050 **Western Distribution Center** 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. AUG 2017

ORDER NUMBER

• 50,000 hour rated life



PRODUCT DESCRIPTION

• Factory-Sealed LED Light Engine

Suitable to install in all directions
120V Direct Wire - No Driver Needed
Smooth and Continuous ELV Dimming

• 360° Horizontal Rotation, 90° Vertical Aiming

• Photo/Motion Sensor Compatible (Sold Separately)

. • [Î] •

FEATURES

Die cast aluminum factory sealed housings with patent pending design for a water and dust proof IP66 rated outdoor luminaire