



OLYMPIA FAUCETS, INC.

3325 S. Garfield Ave. Commerce, CA 90040 (888) 772-7701 www.olympiafaucets.com

Tools:









Adjustable Wrench Plumbers Putty

Sealant Tape

Model Number: L-7240, L-7241, L-7242, L7245

L-7270, L-7271, L-7272


Warnings and Notes:

Check with local plumbing code requirements before installation. This product should be installed by a local listed plumber.

Do not use plumbers putty on threads.




Two Handle Lavatory Faucet





(1) Shut off the water supply. Remove old faucet. Clean mounting surface in preparation for new faucet.




(2) Place the faucet in position on the sink. Slide the crowfoot washer through shank from underneath of the mounting surface and tighten with small plastic locknut with the help of 1-3/32" socket.











"DO NOT USE THREAD SEALANTS, TEFLON TAPE ONLY" "NO USE SELLADORES DE ROSCA, UTILIZAR SOLO CINTA DE TEFLON"




- 1) a. For brass pop-up: Remove flange from drain body.
- b. For 50/50 type pop-up: Remove rubber gasket, flat washer, and lock nut from metal drain body.




(2) a. For brass pop-up: Place a ring of plumbers putty on the bottom of the flange and apply Teflon tape on threaded tailpiece. Thread tailpiece to drain body. Insert flange through drain hole and attach drain body to flange from underneath the sink.


b. For 50/50 type pop-up: Place a ring of plumbers putty on the bottom of the flange. Insert drain body through drain hole. Thread rubber gasket, flat washer, and lock nut onto drain body. Apply Teflon tape only on the threaded area and attach tailpiece to drain body. Please Note: Use Teflon tape only on all thread connection areas. Using pipe thread sealant might weaken material structure and cause leaks.




(3) Ensure the pivot rod hole on the pop-up body faces toward the back of the sink. Tighten the lock nut securely with a wrench.




(4) Connect pop-up tail piece to the trap (check manufacturer's instruction for installation) and remove the excess plumbers putty.



(5) Remove pivot rod nut from pop-up body and ensure the washer is in place. Insert pivot rod and tighten rod nut back to pop-up body.



(7) Connect lift rod strap to pivot rod by using clip. Tighten thumbscrew to connect lift rod strap to pop-up lift rod.




(6) Push pivot rod down and insert drain plug carefully. Test to ensure drain plug works properly.

Exploded Drawing:

* Note: Please specify finish/color when ordering.

	ITEM#	DESCRIPTION
G	OP-430030*	1.2 GPM Aerator
Н	OP-630004*	50/50 Pop-Up Drain Assembly (For L-7240,L-7270)
1	OP-630002*	Brass Pop-Up Drain Assembly (For L-7242,L-7272)
J	OP-630011*	50/50 Push Down Drain With Overflow (For L-7245)
K	OP-430005	Hole Cover (For L-72X1,L-7245)
1	OP-490029	3/32" Allen Screw

	ITEM#	DESCRIPTION
A1	OP-190010C, H*	Lever Handle Cold, Hot (For L-724X)
A2	OP-190015C, H*	Lever Handle Cold, Hot (For L-727X)
В	OP-490040	Bonnet Nut
С	OP-390004	Cartridge-Brass Post
D	OP-490041	Springs & Seats
E	OP-530007	Small plastic locknuts & crowfoot washers
F	OP-590001	Supply Nut





For more care information or trouble shooting inquiries about your Olympia product, Please call:

OLYMPIA FAUCETS, INC. (888) 772-7701

Monday-Friday 8 AM to 8 PM EST (5 AM to 5 PM PST)

www.olympiafaucets.com