

# INSTALLATION INSTRUCTIONS

END-HUNG (STE) &  
REAR-HUNG (STR)  
TUB SEAT

*This seat should be installed as an assembled unit.*

**PLEASE READ THESE INSTALLATION INSTRUCTIONS THOROUGHLY PRIOR TO INSTALLING THIS SHOWER SEAT**

**IMPORTANT: THIS PRODUCT SHOULD ONLY BE INSTALLED BY QUALIFIED AND TRAINED PERSONNEL**


FAILURE TO FOLLOW THESE INSTRUCTIONS COULD LEAD TO IMPROPER INSTALLATION OF THE SHOWER SEAT, STRUCTURAL AND/OR WATER DAMAGE TO THE WALL AND IN-WALL SUPPORT STRUCTURES, AND/OR SERIOUS BODILY INJURY IN USE. IN ADDITION, ALL WARRANTIES, EXPRESS OR IMPLIED, WILL BE NULL & VOID DUE TO IMPROPER INSTALLATION OF THIS PRODUCT. THE MANUFACTURER DOES NOT ASSUME ANY LIABILITY FOR DAMAGE RESULTING FROM SERVICES PERFORMED BY OTHERS, OR FAULTY INSTALLATION, MISUSE OR MISAPPLICATION OF GOODS.

THIS PRODUCT IS DESIGNED TO MEET OR EXCEED ALL LOAD REQUIREMENTS ESTABLISHED IN THE AMERICANS WITH DISABILITIES (ADA) ACT AND/OR FEDERAL SPECIFICATION WW-P-541/8b AT 250 POUNDS OF FORCE. THE PERFORMANCE OF THIS PRODUCT IS SIGNIFICANTLY IMPACTED BY THE STRENGTH AND CONSTRUCTION OF THE WALL TO WHICH IT IS ATTACHED.

TO ASSURE PROPER AND SAFE INSTALLATION, THIS SHOWER SEAT MUST BE INSTALLED INTO A MINIMUM 2" THICK, SOLID WOOD, IN-WALL BACKING MATERIAL. MAKE CERTAIN IN-WALL BACKING COMPLIES WITH ALL LOCAL BUILDING CODE REQUIREMENTS.

## 1. Determine the desired tub seat location.

### STE Series




Remove the tub seat from the shipping carton.

Locate the seat in its proper position on the tub.

**STE Series:** Position the Tub Seat so that when mounted to the tub wall, the end opposite to the tub hinges rests securely on the Tub Dam or Apron.

### STR Series



**STR Series:** Position the Tub Seat so that when mounted to the tub wall, the two sides adjacent to the tub hinges both rest securely on the Tub Dam or Apron.


# INSTALLATION INSTRUCTIONS

END-HUNG (STE) &  
REAR-HUNG (STR)  
TUB SEAT

## 2. Mounting the tub seat to the wall.

Use six (6) #12 x 2½" stainless steel screws (supplied by manufacturer) to secure mounting hinges to the wall.

STE Series




With the two hinges placed against the tub wall, mark the three (3) hole locations for each hinge. Remove the seat from the tub.

Using a 1/8" Carbide tip drill bit (not provided), create three mounting holes for each the right and left mounting hinges.

Use clear silicone sealer at each hole location to prevent water damage to existing structures as desired.

STR Series



Tightly secure the two mounting hinges to the wall **AND INTO 2" THICK, SOLID WOOD IN-WALL BACKING MATERIAL**, using six (6) #12 x 2-1/2" stainless steel screws (supplied by manufacturer).  
*Tighten screws completely **AFTER** all screws are in place.*

Once secured to the tub, make certain the seat does not shift from its set position in any direction before use.

***THIS COMPLETES THE INSTALLATION OF THE STE or STR TUB SEAT.***

Hardware provided:

(6) #12 X 2-1/2" Phillips Pan Head sheet metal screws

Tools required:

Power drill, 1/8" Carbide tip drill bit, marking pen/pencil, level, #3 phillips driver.