

# SPEAKMAN® S-1495-AF

## Exposed Anti-Scald Balanced Pressure Shower

### FEATURES:

- Sentinel Mark II exposed anti-scald balanced pressure Shower.
- Brass lever handle.
- Adjustable temperature limit stop.
- Chrome plated cast brass body.
- Pressure balancing & ceramic temperature regulating cartridge with built-in check valves.
- ½ in. NPTF inlets.
- Vandal-resistant standard.
- Exposed anti-scald balanced pressure shower.
- Adjustable stops and supply connections from floor, ceiling or wall.
- 7-1/2 in. center to center.
- Polished chrome plated brass gooseneck with supporting strap.
- S-2292 showerhead with flow control device reduces flow to 2.5 gpm (9.46 L/min) maximum

### FINISH:



PC

### COMPLIANCE:

- Valve meets ASSE 1016 standard and ASME A112.18.1/CSA B125.1 standard.
- Showerheads meet ASME A112.18.1/CSA B125.1 standard.

### OPTIONS: Add suffix to model #

- Less showerhead  -LH
- S-2251 showerhead  -1
- S-2253 showerhead  -3
- S-2272-E2 showerhead  -5

### WARRANTY:

- 5 year limited



**DIMENSIONS:** NOTE: 1. Dimensions are in inches (millimeters) and subject to change without notice. 2. Unit can be installed with ceiling, floor or through the wall supplies. 3. 1/2" NPT female inlets.

