## Nuda 50 bilateral floor white

## T083708

Design By Ernesto Gismondi Collection Outdoor	<ul> <li>Electronic driver integrated in bo</li> <li>Standard non dimmable</li> <li>For dimming options, please constructions</li> </ul> Packaging 1 Box	>80 50000Hrs On/Off 120V MAGTECH - 1 x LA1012-36-C0350 B0-U2-G0 anector for the main connections r ground fixing by means of included lock bolts and dowel
Outdoor	Power consumption         Led type         CCT (Correlated Color Temperature         CRI (Color Rendering Index)         Life expectancy         Control type         Input Voltage         Driver         BUG Rating         Provided with IP65 cables and co         • Provided with IP65 cables and co         • Standard non dimmable         • For dimming options, please construction         • Packaging         1 Box	8W         6X6.8W Array*         3000K         >80         50000Hrs         0n/Off         120V         MAGTECH - 1 x LA1012-36-C0350         B0-U2-G0
Outdoor	Led type CCT (Correlated Color Temperature CRI (Color Rendering Index) Life expectancy Control type Input Voltage Driver BUG Rating Peatures & Accessories • Provided with IP65 cables and co • Mounting plate contains holes for • Electronic driver integrated in boo • Standard non dimmable • For dimming options, please conservations • Packaging 1 Box	6X6.8W Array*         3000K         >80         50000Hrs         On/Off         120V         MAGTECH - 1 x LA1012-36-C0350         B0-U2-G0
	CCT (Correlated Color Temperature CRI (Color Rendering Index) Life expectancy Control type Input Voltage Driver BUG Rating Features & Accessories • Provided with IP65 cables and co • Mounting plate contains holes fo • Electronic driver integrated in bo • Standard non dimmable • For dimming options, please cons Packaging 1 Box	3000K         >80         50000Hrs         On/Off         120V         MAGTECH - 1 x LA1012-36-C0350         B0-U2-G0
	CRI (Color Rendering Index) Life expectancy Control type Input Voltage Driver BUG Rating Peatures & Accessories • Provided with IP65 cables and co • Mounting plate contains holes fo • Electronic driver integrated in bo • Standard non dimmable • For dimming options, please cons Packaging 1 Box	>80 50000Hrs On/Off 120V MAGTECH - 1 x LA1012-36-C0350 B0-U2-G0 anector for the main connections r ground fixing by means of included lock bolts and dowed dy
	Life expectancy Control type Input Voltage Driver BUG Rating Peatures & Accessories • Provided with IP65 cables and co • Mounting plate contains holes for • Electronic driver integrated in boo • Standard non dimmable • For dimming options, please conservations • Packaging 1 Box	50000Hrs         On/Off         120V         MAGTECH - 1 x LA1012-36-C0350         B0-U2-G0         anector for the main connections         r ground fixing by means of included lock bolts and dowe dy
	Control type Input Voltage Driver BUG Rating Peatures & Accessories • Provided with IP65 cables and co • Mounting plate contains holes fo • Electronic driver integrated in bo • Standard non dimmable • For dimming options, please cons Packaging 1 Box	On/Off 120V MAGTECH - 1 x LA1012-36-C0350 B0-U2-G0 anector for the main connections r ground fixing by means of included lock bolts and dowe dy
	Input Voltage Driver BUG Rating Peatures & Accessories • Provided with IP65 cables and co • Mounting plate contains holes fo • Electronic driver integrated in bo • Standard non dimmable • For dimming options, please cons Packaging 1 Box	120V         MAGTECH - 1 x LA1012-36-C0350         B0-U2-G0         Innector for the main connections         r ground fixing by means of included lock bolts and dowed         dy
ate	Driver BUG Rating Peatures & Accessories • Provided with IP65 cables and co • Mounting plate contains holes fo • Electronic driver integrated in bo • Standard non dimmable • For dimming options, please cons Packaging 1 Box	MAGTECH - 1 x LA1012-36-C0350 B0-U2-G0 nnector for the main connections r ground fixing by means of included lock bolts and dowe dy
ate	BUG Rating Features & Accessories • Provided with IP65 cables and co • Mounting plate contains holes fo • Electronic driver integrated in bo • Standard non dimmable • For dimming options, please cons Packaging 1 Box	B0-U2-G0 nnector for the main connections r ground fixing by means of included lock bolts and dowe dy
ate	Features & Accessories  Provided with IP65 cables and co Mounting plate contains holes for Electronic driver integrated in bo Standard non dimmable For dimming options, please cons  Packaging 1 Box	nnector for the main connections r ground fixing by means of included lock bolts and dowe dy
iate	<ul> <li>Provided with IP65 cables and co</li> <li>Mounting plate contains holes for</li> <li>Electronic driver integrated in bo</li> <li>Standard non dimmable</li> <li>For dimming options, please cons</li> </ul> Packaging 1 Box	r ground fixing by means of included lock bolts and dowe dy
	1 Box	
		.6 lbs - 29 cm x 29 cm x 64 cm / 5.26 kg
Luminaire weight		
7.94 lbs / 3.6 kg		
Warranty		
	Luminaire weight 7.94 lbs / 3.6 kg Warranty	7.94 lbs / 3.6 kg

