

Undermount Ramp Specifications

Material:	Composite Stone
Color:	Gloss White
Weight:	26 pounds
Handcrafte	d in Miami Lakes, FL

Installation Instructions

Marble-Lite does not provide templates for undermounting. Please have the product on site for the countertop fabricator. Please use construction adhesive that iscompatible with our product and countertop material, such as polyurethane adhesive, Sika 221, or equivalent, to adhere sink to counter. Adhesive must be appropriate strength for the weight of the product being installed. Do not use clear kitchen & bath silicone to adhere sink to counter.

1. Take measurements for the opening of the undermount sink. We recommend leaving 1/8" overhang on all sides. Fabricator should open and finish edges of hole.

2. Dry fit the top of the sink to the underside of the counter and mark the counter around the sink's mounting flange.

3. Use isopropyl alcohol and a lint-free cloth to clean the sink's mounting flange and the underside of the countertop before applying adhesive to the mounting flange.

4. Glue bowl to marked area on the underside of the counter.

5. Secure 2 clips on each side of the sink bowl. Marble-Lite does not provide undermount clips,

the mounting flange will accommodate most commonly used clips.

7. Flip the countertop and seal the seam with color matched caulk or clear silicone.

8. Install tube provided in packaging into bottom of sink. Do Not overtighten as it may damage the drain.

9. Test for plumbing leaks.



Marble-Lite 9920 NW 79th Ave Hialeah Gardens, FL 33016 www.marblelite.com