OWNER'S MANUAL





Installation instructions Undermount / Topmount Sinks

General Recommendations:

Read installation and maintenance instructions, thoroughly before installation. Be sure to use proper tools and always wear personal safety accessories for your protection

Tools and Materials needed:

- Tape Measure
- · Pencil (NOT ink)
- · Silicone Adhesive Sealant
- Rags

- Denatured Alcohol
 - Ear Protection
 - Eye Protection
 - Hacksaw/Jigsaw
 - Mounting clips (included)

SINK FEATURES

- Thick Stainless Steel
- 304 Nickel-Bearing Content
- · Long-lasting,easy-to-clean,satin finish
- Sound-deadening insulation
- · Elegant and functional drain griives
- · Rear drain placement

Care and Maintenance ALWAYS

- Clean everyday by thoroughly rinsing with a mild soap and warm water and wipe dry.
- Rub lightly with a soft cloth in the direction of grain lines on a regular basis for additional preventive cleaning.
- Keep the sink free of any standing water as this can cause a buildup of mineraldeposit, which can affect the appearance of your sink.
- Any stubborn stains should be removed by scrubbing in the direction of the grain with a mild abrasive such as Comet
- Always rinse the sink after using any cleaning agent and wipe dry.Clean any mineraldeposits built up over time with a mild solution of vinegar and water followed by a horough flushing with water.
- Remove any scratches with a Scotch-brite pad and cleaning agent rubbing in thedirection of the grain.

NOT RECOMMENDED FOR MIRROR FINISH.

NEVER

- Leave water spots, steel cookware or utensils in the sink for lengthy periods ; iron particles often develop rust spots in the stainless steel surface.
- Use a steel wool or scoring pad as it damages the sink surface and causes discoloration.
- Let household cleaning agents or bleach sit in your sink for long period of time as this may ruin the finish of your sink.
- Leave rubber mats, sponges, or cleaning pads in the sink for long period of time as this may ruin the finish of your sink.
- Use any drain cleaning products containing sulfuricacidor hydrochloric acid asthis will attach the sink.Silver cleaners can also contain acids that will damage the sink surface.
- · Use the inside of the sink as cutting surface.

Installation Instructions For Undermount Sink OPTION A

Please carefully read complete instructions before beginning installation.Note:These instructions are for installation with solid surface,composite material countertors. We recommends professional countertop installers and is not responsible for damage to the countertop or sink during installation.

1.Unpack the new sink and check the contents of the materials supplied : Sink, Mounting brackets, strainer and Cutout template(depending on model).

2.Supplied cutout template provides follow options of installation: A.Flush mount : Sink edge is flush with countertop opening.(FIGURE 1)



3.Cut out the appropriate template for your sink model and desired installation option. Place template in desired position on countertop, locating center of the bowl over cabinet and faucet holes.

4. Trace the outline of the template and cut countertop acoording to templated outline using appropriate cutting tools. Template is for guide only. Use physical sink to ensure accurate cutout opening. (FIGURE 2)



FIGURE 2

5.Locate the drill holes on the underside of the countertop, approximately1"from edge of the sink to be installed.
Holes should be evenly spaced approximately 6" to 8" apart starting from every corner as shown in (FIGURE 3).
It is recommended to install a faucet at this point before installing the sink.



FIGURE 3

6.Loosely attach mounting brackets to the countertop,parallel to the cutout opening using the supplied mounting screws and nuts.Mounting screws with brass inserts are supplied with the sink,however,countertop material vary and the correct type of fasteners should be recommended by your installer or supplier.

7.Clean sink flange and underside of cutout area of countertop, making sure that the area is smooth and free of grease.Apply continuous bead of silicone caulk evenly on top of sink flange. (FIGURE 4)

8.Position and align sink over the countertop opening and press sink onto countertop.Turn bent end of mounting bracket to snug over the sink rim.(FIGURE 5)

9.Check alignment of sink again and tighten fasteners to secure sink.

10.Wipe away excess silicone caulk with damp cloth.Connect drain and water supply according to manufacturer's instruction.(FIGURE 6)

- 1.Basket
- 2.Metal Strainer
- 3.Screw
- 4.Rubber seal
- 5.Rubber gasket
- 6.Main body







FIGURE 5



Installation Instructions For Topmount Sink OPTION B

Please carefully read complete instructions before beginning installation. Note:These instructions are for installation with solid surface,composite material countertors. We recommends professional countertop installers and is not responsible for damage to the countertop or sink during installation. 1.Unpack the new sink and check the contents of the materials supplied : Sink,

Mounting brackets, and Cutout template(depending on model).

2.check the cut out templated is the same as bowl inner size.

A.Flush mount : Sink edge is flush with countertop opening. (FIGURE 1)



3.Cut out the appropriate template for your sink model and desired installation option.Place template in desired position on countertop,locating center of the bowl over cabinet and faucet holes.

4. Trace the line of the template and cut countertop according to templated size. using appropriate cutting tools. Template is for guide only. Use physical sink to ensure accurate cutout opening. (FIGURE 2)



FIGURE 2

5.Use waterproof glue under sink edge. Press sink on the kitchen marble. To make sure the sink fix on marble is ok.('FIGURE 3)



6.Verify that the sink fits perfectly. The lip of the sink should be resting on the countertop.(FIGURE 4)



7.Make proper water and waste pipe connections.(FIGURE 5)



FIGURE 5