

ASSEMBLY INSTRUCTIONS




MODEL RTA-S18

Thanks for purchasing one of our products.


Please read carefully the assembly instructions before the installation.


Please save this manual for future reference.




MODEL RTA-S18








PARTS LIST








-SCREWS LIST

PART	QTY.	ITEM	
Α	28	3X12 MM	Фаннь
В	24	3X15 MM	Drittino
С	7	6X12 MM	
D	18	4X14 MM	Onn
Е	8	4X35 MM	Dannann-
F	8	6X40 MM	(1)→)

PART	QTY.	ITEM	
G	6	6X25 MM	⊕≕∑
	1		
	1		£ \$

HOW TO ASSEMBLE USING BOLTS AND CAM LOCKS:





If the panel already comes with the cam lock inserted, make sure is aligned:

MISALIGNED:
TURN CAM LOCK
TO POINT TOWARDS
THE HOLE

CORRECT




GENERAL ASSEMBLY TIPS AND TROUBLESHOOTING DURING ASSEMBLY:


- *Before you start assembling, make sure you have all the parts and necessary hardware by doing a quick inventory.
- *Follow the assembly instructions step by step, and do not skip any unless advised to do so by RTA PRODUCTS' Customer Service.
- *On each step, and to avoid misalignments, always leave screws loose, and do not tighten them until all are in place.
- *In wood panels, the laminate might be covering the holes.


 If there are no visible holes: Pass the tip of your finger around the area where the hole should be, and press against the surface to feel the indentation.

 If the hole looks too small for the screw of bolt: carefully perforate the laminate with the tip of a pen.



*In wood panels, some might have inserts that look like screws. Those inserts are either nuts or cam locks. Make sure they are aligned to receive the screws or bolts.






*Make sure to use the correct screws or bolts, and do not overtight them.
Using wrong screws or overtighting them might cause damage to the parts,
and such damage is not covered by the product's warranty.



RTA-S18 P.7

ASSEMBLY STEPS:



• Open the slider (22) and hold it as shown. Press the locking lever up hard with the tip of your thumb to separate sliders into the outer rail (22a) and the inner rail (22b). (22a) will be used on step# 4, and (22b) on step# 25.

Inner Rail


° () O


0000

<u>] 0 0 0</u>


Outer Rail


22A






■First screw bolts F & G to the Left Panel (1) and Right Panel (2), then assemble the Back Panel, Bottom Panel and Middle Panel (3, 5 & 7) as shown and as explained in page 5.
PLEASE PAY ATTENTION TO WHERE EACH BOLT IS USED.








8


• First screw bolts F & G to the Top Panel (4), then assemble it to the Left Panel, Right Panel and Back Panel (1, 2 & 3) as shown and as explained in page 5.













x2

(A)2000000




■Press the Metal Ring (24G) into the hole of the Small Drawer Front Panel (8) from the face of the panel. Use Screws (B) to assemble the Lock (24D) to the Small Drawer Front Panel (8).

Make sure the rod on the lock is facing down, and the key must turn counter-clockwise.




■ Place the drawer upside- down as shown and use screws B to assemble the "L" shaped Sliders to the Small Drawer Left & Right Panels (9 & 10) as shown.


IMPORTANT: REFER TO THE DRAWINGS FOR THE CORRECT POSITION OF THE SLIDERS. If they get installed incorrectly, the drawer will raise 1" with a gap at the bottom and it will hit the top of the cabinet making it impossible to close!




17



• Use screws A to fix the Folder Hangers (19) to the File Drawer Front Panel and Back Panel (15 & 18).




18





SCREWS

■Use screws C & D to assemble the L Bracket (21) to the File Drawer Front Panel (15).

Fix the Drawer Wheel (20) to the L Bracket (21) with the nut and tighten well.








■ Insert the Hanging Files Tubes (23) and screw into File Drawer Front Panel (15).

Attention: Do not over tighten them, as doing so will cause damaged to the panel.




RTA-S18 P.15

26


Tighten any and all screws.

Carefully slide drawers onto rails and push firmly and evenly until they are completely closed.






Make sure inner silver ball bearing slide is at the front of the slide mount and in lock position(over the hump), as shown.



Align both sides of slide runners to slide mounts' openings,then slide all the way in.Apply small force to insert completely if needed

27



■ Enjoy your unit!

CARE AND MAINTENANCE

English

- DO NOT EXPOSE THE SURFACES TO DIRECT SUNLIGHT OR EXTREME ENVIRONMENTAL CONDITIONS. ANY DAMAGE RESULTING FROM SUCH EXPOSURE IS NOT COVERED BY THE PRODUCT'S WARRANTY.
- THE PREFERABLE METHOD TO CLEAN THE SURFACES IS TO WIPE THEM USING A SOFT CLOTH DAMPENED WITH A SOLUTION SOAP AND WATER, THEN DRY WITH A CLEAN TOWEL.
- DO NOT SPRAY SOLVENTS OR CLEANING AGENTS DIRECTLY OVER THE SURFACES, STRUCTURAL TUBES OR METAL PARTS.
- DO NOT LEAN, SEAT OR STAND OVER THE UNIT.
- DO NOT ALLOW CHILDREN TO PLAY OVER/UNDER THE UNIT, NOR ALLOW THEM TO REACH INSIDE ANY COMPARTMENTS WITHOUT THE SUPERVISION OF AN ADULT.
- BEFORE MOVING OR TRANSPORTING THE UNIT, MAKE SURE THAT:
- ALL HEAVY OBJECTS OR THAT MIGHT FELL OFF ARE REMOVED FROM THE UNIT.
- IF THE UNIT ARE ON CASTERS (WHEELS), MAKE SURE THAT ALL ARE UNLOCKED.
- THE UNIT MUST BE HANDLED BY AT LEAST 2 PERSONS.
- WHEN LIFTING THE UNIT, USE BOTH OF YOUR HANDS, AND BEND YOUR KNEES. REMEMBER TO ALWAYS LIFT WITH YOUR LEGS, NOT YOUR BACK.
- IN CASE OF DAMAGE TO ANY PARTS, NOTIFY THE VENDOR AS SOON AS POSSIBLE.
- IN CASE OF GLASS BREAKAGE (IF THE UNIT HAS A GLASS TABLE TOP OR PARTS MADE OF GLASS) DO NOT HANDLE THE BROKEN GLASS WITH YOUR BEAR HANDS, AND CONTACT THE VENDOR IMMEDIATELY. DO NOT ALLOW CHILDREN NEAR THE BROKEN GLASS.