

INSTALLATION INSTRUCTIONS

LED PENDANT

Please read carefully and save these Instructions, as you may need them at a later date.

CAUTION

WARNING: Risk of Fire, Min 90°C supply conductors. Consult a qualified electrician to ensure correct branch circuit conductor.
Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.
Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the Installation Instructions.

ASSEMBLY AND INSTALLATION

1. Shut off the power at the circuit breaker and remove existing fixture, including the crossbar.
2. Remove the mounting screw from the fixture.
3. Secure the mounting back plate to the outlet box using Junction box screws. The side of the mounting bar marked "GND" must face out.
4. Properly secure the safety cord to the bracket on mounting bar to temporary hang the fixture in place.
5. Adjust the fixture wire length by pushing the cable gripper on the canopy and pulling the wire as desired.
 - a) Retract these wires close to a desirable length to within the canopy before securing the fixture in place. Using the cable gripper to adjust more than 18" of wire length is not desirable.
 - b) Warning: Shortening these cables without professional helps or electronic background is not advisable. Any modifications to the fixture may result in voiding the warranty of the product.
6. Connect the Driver Input wires to outlet box wires, making sure that all wire connectors are secured. If your outlet box has a green or bare copper ground wire, connect the fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to the back plate using the green screw provided. After wires are connected, tuck them carefully inside the outlet box.
7. Secure the canopy to the mounting bar using the mounting screw.
8. Make final adjustment to desire the cable length.

DIMMING

This fixture features electronic Triac dimming capabilities. To utilize TRIAC dimming: use wires black (hot), white (neutral) and bare copper ground wire (ground).

