

SPECIFICATIONS

COS-KS6U36 Range Hood





Size	36 Inch
Mounting Type	Under Cabinet
Controls	Soft Touch with LCD Display, Remote
Filters	3 x Stainless Steel Baffle Filters
Material	430 Grade Stainless Steel
Air Flow	500 CFM
Noise Level	45 dB*
Vent Style	External
Lighting	2 x Front LED
Voltage	110V / 60Hz
Wattage	241W
Included Components	Bulb(s), Damper, Exhaust Vent, Fan Hardware, Installation Kit, Power Cord, Wireless Remote

COS-KS6U36

Presenting this modern range hood, Cosmo's COS-KS6U36 is powered by 500 CFM of suction, 2 LED lights and ARC-FLOW® Stainless Steel Permanent Filters.





LED Lighting

Features

- \cdot Designed for under cabinet mounting
- \cdot 3 fan speeds
- 500 CFM airflow capacity
- \cdot Soft touch controls with LCD display and remote
- ARC-FLOW® Permanent Filters
- 2 front LED lights
- \cdot Noise level as low as 45 dB*
- \cdot Top or back vented



See Page 2 for dimensions


For more information, please visit: www.cosmoappliances.com

* Noise level as low as 45 dB on lowest fan speed with rigid ducting (sold separately) under optimal conditions



DIMENSIONS

COS-KS6U36 Range Hood



35 7⁄16" (900 mm)

Dimensions (WxDxH): 35.4" x 22.8" x 6"

For more information, please visit: www.cosmoappliances.com