

PRODUCT NAME:Linear LED ITEM NUMBER: 55534/55535/55536

Please consult your electrician for hanging fixture and wiring.



WARNING: Wires need to be connected to driver found in canopy and should not be connected directly to power source or a short may occur

Bulbs (integrated): 90-305V Input Integrated

IMPORTANT: Turn off the power at the main fuse or circuit breaker box before starting installation 10) (A)Wire Nuts (B)MJL-HXY (C)mounting panel white supply wire 4.) ground around black supply wir blac Step4:Pull the supply wires and house ground wire out from the outlet box before attaching wall plate to outlet box ,Make electrical connections, connect the black fixture black wire to the black supply wire and the white fixture wire to the white supply wire using wire nut.Connect the fixture ground wire to the supply ground wire together using wire nut.Wrap all wire connections with electrical tape to ensure secure connection. fixture screws 5.)

Step5:Place the fixture base over the mounting wall plate and secure it to the wall plate by using four fixture screws.

MADE IN CHINA Page 1 of (2)



Step 3:Replace the mounting wall plate over outlet box, align the narrow end of each keyhole slot with its respective wall anchor. Feed the anchor screws through keyhole slots and thread them into the wall anchors until wall plate is flush against the wall. Additionally, fasten the wall plate to thread holes in outlet box using two outlet box screws, as shown.

Cleaning & Care: Clean with soft cloth and a mild detergent Do not use abrasive cleaner.

Page 2 of (2)